

800萬像素30倍光學快速球監視器 AVA810

戶外防水IP65

30倍電動光學變焦，自動對焦

SONY IMX415 1/2.8" CMOS鏡頭

800萬像素

3D DNR, 數位WDR

3D智慧定位，254個可程式預設



特色功能

- ▶ 30倍電動光學變焦，自動對焦
- ▶ SONY IMX415 1/2.8" CMOS鏡頭
- ▶ 攝影鏡頭解析度：800萬像素
- ▶ 3D DNR, 數位WDR
- ▶ 3D智慧定位，254個可程式預設
- ▶ h.265+/H.265/H.264 主要設定檔編碼，三個同步視訊串流
- ▶ 支援 ONVIF 2.6
- ▶ 背光補償和自動增益控制 (AGC)

Focal length	F=4.3-129mm 30X
IR LEDS	9pcs OSRAM IR Array LEDs, IR Distance 150M
Aperture Range	F1.5~F1.9
Zoom speed	Approx 3s(Optical Wide-Tele)
Frame rate	Mainstream: 8MP3840x2160@20fps, 6MP3072x2048@30fp 4MP2688X1520@30pfs, 3MP2304x1296@30fps, 2.0MP 1920X1080@30fps
Min. Illumination	Color: 0.01Lux@(F1.6, AGC ON) B/W: 0.001Lux@(F1.6, AGC ON)
WDR	128db
HDR	128db
S / N ratio	≥70dB (AGC OFF)
AGC	Auto / Manual
White balance	Auto/Manual/ATW/Indoor/Outdoor/Daylight lamp/Sodium lamp
數位降噪	DNR,3DNR
Exposure mode	Auto/Manual/shutter mode (shutter range variable)
Shutter speed	1/2 - 1/20,000s
Day & Night	Day / Night / External control (IR Cut Filter)
Number of preset	254
PTZ function	4 Patrol、4 Pattern、Pan scan
3D Positioning	Click centering, Zoom by mouse dragging
Streams	Dual streams
Bitrate	CBR/VBR, bitrate: 32Kbps~10Mbps variable
影像壓縮格式	H.265+/H.265/H.264
聲音壓縮格式	G711
OSD	Support zoom、camera name、time displav. OSD position can be adjusted
P2P	Android、IOS
Human detection	YES
Motion detect	Support
Protocol	TCP/IP, HTTP, NTP, IGMP, DHCP, UDP, SMTP, RTP, RTSP, ARP, DDNS, DNS, P2P,Support Private protocol XM NVR, Hikvison Protocol, Work iVMS-4200-UC2
Power Supply	DC12V2A
weight	7KG
Package size	27*26*40CM
工作環境	-30°C ~60°C, Humidity≤90%RH(Unsupport-condensing)